

INTRODUCTION

1.1 Features

- PCI Express 2.0 x4
- Provides two SuperSpeed 10 Gbps USB 3.2 Gen 2 Type-C ports and two Type-A ports to support total transfer bandwidth up to 20 Gbps
- Compliant with Intel's eXtensible Host Controller Interface (xHCI) Specification Revision 1.1
- Supports Multiple INs
- Supports the following speed data rates:
1.5 Mbps/12 Mbps/480 Mbps/5 Gbps/10 Gbps
- Supports 4 downstream ports for all speeds
- Hot-swapping feature allows you to connect/disconnect devices without powering down the system

1.2 System Requirements

- Windows 8.x/10 (32/64 bit)
- macOS X 10.10 or later
- Linux 3.5 or later
- One available PCI Express x4, x8 or x16 slots

1.3 Package Contents

- 1 x PCIe Dual Bus USB 3.2 4-Port Controller Card
- 1 x Quick Installation Guide

Note: Contents may vary depending on country/market.

GETTING STARTED

2.1 Hardware Installation

1. Turn off the power to your computer.
2. Unplug the power cord and remove your computer's cover.
3. Remove the slot bracket from an available PCI Express x4 (x8, x16) slot.
4. To install the card, carefully align the card's bus connector with the selected PCIe slot on the motherboard. Push the board down firmly.
5. Replace the slot bracket's holding screw to secure the card.
6. Secure the computer cover and reconnect the power cord.

2.2 Driver Installation for Windows and macOS

1. Drivers are embedded into Windows 8.x/10 and macOS; the drivers can be installed automatically.

