

INTRODUCTION

1.1 Features

- Supports 2 x USB 3.2 Gen 2 ports
- Supports PCIe 3.0 x2
- Compliant with PCI Express Base 3.0 Specification
- Compliant with USB 3.2 Specification Revision 1.0
- Up to USB 3.2 Gen 2 10 Gbps Bandwidth Performance with Low Latency
- Compatible with USB 3.2, USB 3.1, USB 3.0 and USB 2.0 devices
- Supports Multiple INs
- Compliant with UASP Revision 1.0
- Max. current output 3A per port
- 15-pin SATA Power connector

1.2 System Requirements

- Windows 8.x/10 (32/64-bit); Windows Server 2012
- Mac OS X 10.10 or later
- Linux 3.5 or later
- One available PCI Express x4, x8 or x16 slots

1.3 Package Contents

- 1 x PCIe USB 3.2 Gen 2 Host Adapter
- 1 x Quick Installation Guide
- 1 x Low Profile Bracket

GETTING STARTED

2.1 Hardware Installation

1. Turn off the power to your computer.
2. Unplug the power cord and remove your computer's cover.
3. Remove the slot bracket from an available PCI Express slot (x4 x8, or x16) .
4. To install the card, carefully align the card's bus connector with the selected PCIe slot on the motherboard. Push the board down firmly.
5. Replace the slot bracket's holding screw to secure the card.
6. Secure the computer cover and reconnect the power cord.

2.2 Driver Installation

1. Drivers are embedded into Windows 8.x/10 and macOS; the drivers can be installed automatically.

